STOCK PREPARATION

STOCK CHEST AGITATOR (AG)

Stock Chest Agitators are energy efficient agitators that find application in all type of Pulp storage chests, including High Density Towers, Mixing Chest & Machine Chest. Agitator will be complete with SS Propeller, En8 shaft, CI Cone, CI Pulleys, CI grouting ring and antifriction bearings.



Salient Features:

- All parts in contact with stock made of stainless Steel.
- Highly energy efficient.
- Provision for adjusting the vane angle to suit specific process requirement of gentle or strong agitation.
- Sturdy design incorporate Bearings & Glands.
- Located outside, optimally designed adjustable propeller blades.
- Easy installation and Economic in cost.
- Various models are designed & manufactured as per chest volume.

Technical Specifications:

Agitator Size	Horizontal Chest		Vertical Chest		
	Volume (M ³)	Motor Rating (kW)	Volume (M ³)	Motor Rating (kW)	Vane Diameter (mm)
GAG 50/60	25-100	11-15	7-15	5.5-7.5	500/600
GAG 75/85	100-275	15-22	20-40	11-15	750/850
GAG 100/115	275-500	30-37	45-80	18.5-22	1000/1150
GAG 135/155	500-700	55	85-155	30-37	1350/1550
GAG 170	700-850	75	155-200	45	1700

Global Paper Machinery & Engg. Co.

Global Paper Machinery & Engg. Co.



82,Ganga Sagar Scheme, 200 Feet Bypass, Sirsi Road, Jaipur-302021 Tel: +91-141-5179040,2470290, Fax: +91-141-5179040

Email: sales@globalpapermachine.com

www.globalpapermachine.com

© Copyright 2006 Global Paper Machinery & Engg. Co. Contact for the detail. Rev 00-0